

DIGIMIC® classic

**Delegates' Conference Unit CMic CSV
with channel selector and voting**



WPF05.0165.E.130319 BRÄHLER ICS is committed to continually improving its products and so reserves the right to make technical modifications without notice.

Description

The fully digital, wired microphone unit CMic CSV in the DIGIMIC system serves as the frontend for verbal communication and more.

The ultra-slim DIGIMIC CMic CSV microphone unit now has integrated a channel selector and voting functions.

A high-resolution graphical OLED display shows the selected channel in the respective language, including Cyrillic, Arabic, or Chinese, in pin sharp detail. The display automatically adjusts to ambient light and is glare-free even in darkened conference rooms.

The clearly structured CMic CSV offers one microphone button for push-to-talk and request-to-speak function, lighting up red when activated. The two integrated loudspeakers provide decentralized voice amplification to increase the speech intelligibility for the delegates.

In addition each CMic CSV is equipped with an amplified headphone socket and corresponding volume control.

As a wired component the CMic CSV has a firmly mounted cable (2.50 m) with a lockable plug.

Technical Data

The CMic CSV complies with international standard IEC60914

Digital Audio

- high quality digital audio:
Sample Rate: 48 kHz
Frequency response: 20 - 20,000 Hz
- OR + 7 language channels

Connectors

- System cable firmly fixed (2.50m, DisplayPort* Connector, lockable)
- Socket for another unit (DisplayPort*)
- Microphone socket (Minicon)
- Headphone socket (stereo/mono), 3.5 mm

Features

- 256 x 32 OLED display (automatic brightness adjustment)
- 5 function keys for channel selection, voting and further functionality
- Illuminated microphone button for indication MIC ON/OFF, REQUEST
- two integrated loudspeakers for decentralized audio amplification
- volume control for headphone

Housing

- housing upper part: anodized aluminum
- housing lower part: plastic, black
- W x H x D: (139 x 22 x 142) mm (5.5 x 0.8 x 5.6) inch
- Weight: 500 g approx.

Other system components

- **CMic** Delegates' Conference Unit classic
- **CChair** Chairpersons' Conference Unit classic
- **DMic** Delegates' Conference Unit with data interface for DDoc
- **DChair** Chairpersons' Conference Unit with data interface for DDoc
- **DDoc** Docking Unit for expansion of DChair and DMic to a wireless conference unit
- **TMD/01** Conference Microphone with ring-shaped live indicator and integrated windshield functionality, gooseneck
- **TM58/6** Conference Microphone with ring-shaped live indicator, gooseneck
- **CM9-x** Adapter cable for connecting D Cen and extension

*DisplayPort is a standardized connection by Video Electronics Standards Association (VESA)